


TLBES 125

Destroçador TLBE/S

MINI GIRATÓRIAS Essencial para trabalhos de limpeza na agricultura, floresta e espaços verdes.

LARGURA


	TRAB.	CORR.	MARTELOS	PESO	PRESSÃO	CAUDAL	
K5 - TLBE - 055	0,54m	2	6 	180kg	220/250 bar	20/45 lts	
K5 - TLBE - 075	0,74m	2	7 	200kg	220/250 bar	30/45 lts	
K5 - TLBE - 095	0,94m	2	8 	220kg	220/250 bar	30/45 lts	
K5 - TLBE - 115	1,14m	2	11 	230kg	220/250 bar	40/60 lts	
K5 - TLBES - 115	1,14m	3	8 	330kg	220/250 bar	60/70 lts	
K5 - TLBES - 125	1,24m	3	8 	350kg	220/250 bar	60/70 lts	

TLBE 095



LIGEIRO 2.500kg a 5.000kg (TLBE)

REFORÇADO 5.000kg a 9.000kg (TLBES)

- Chassis em chapa de aço anti-desgaste;
- Rotor Ø 108mm - 2200 rpm de martelos (TLBE);
- Rotor Ø 140mm - 2200 rpm de martelos (TLBES);
- Correntes dianteiras e traseiras anti-projecção;
- Rolo nivelador traseiro de regulação em altura;
- Patins;
- Motor hidráulico;
- Transmissão lateral por correias;
- Sistema de engate standard.



Rotor/martelos TLBE.



Barras de recorte

Rotor/martelos TLBES.