








Destroçador TLBE/S

Mini-escavadoras

	DIMENSÕES				Peso	Pressão	Caudal
	Larg. Int.	Larg. Total	Corr.	Mart.			
K5 - TLBE - 055	0,54m	0,65m	2	6 	180kg	250 (bar)	30 - 45 (lts)
K5 - TLBE - 075	0,74m	0,85m	2	7 	200kg		
K5 - TLBE - 095	0,94m	1,10m	2	8 	220kg		
K5 - TLBE - 115	1,14m	1,25m	2	11 	230kg	250 (bar)	40 - 60 (lts)
K5 - TLBES - 115	1,14m	1,25m	3	8 	330kg	250 (bar)	60 - 70 (lts)
K5 - TLBES - 125	1,24m	1,35m	3	8 	350kg		

LIGEIRO **2.500kg a 5.000kg (Mod. TLBE)**
 REFORÇADO **superior a 5.000kg (Mod. TLBES)**

Essencial para trabalhos de limpeza na agricultura, floresta, espaços verdes e obras públicas.

- Chassis monobloco em chapa de aço anti-desgaste;
- Rotor Ø 108mm - 2200 rpm de martelos (mod. TLBE);
- Rotor Ø 140mm - 2200 rpm de martelos (mod. TLBES);
- Avental dianteiro e traseiro anti-projecção;
- Rolo nivelador traseiro de regulação em altura;
- Patins;
- Motor hidráulico;
- Transmissão lateral por correias;
- Sistema de engate.