

TLJL

	LARGURA INTERIOR (mm)	LARGURA TOTAL (mm)		MART.		PESO (kg)	POTÊNCIA (cv)
K5-TLJL-160	1640	1800	5	11		780	70-80
K5-TLJL-180	1840	1960	5	12		810	70-80
K5-TLJL-200	2000	2160	5	13		850	70-80
K5-TLJL-220	2240	2400	5	15		900	80-90
K5-TLJL-250	2540	2700	5	17		1000	90-110
K5-TLJL-280	2840	3000	5	20		1110	110-120



1. Rotor martelos dentados.



BARRAS DE RECORTE



TLJL 250

DESTROÇADOR reforçado profissional, polivalente para trituração de restolhos, restos de poda e outros.

- Montagem aos 3 pontos;
- Chassis robusto c/ dupla capota (4+6) 10mm;
- Descentramento hidráulico (pistão autolubrificante);
- Caixa de engrenagem c/ roda livre (1 3/4" Z6);
- Transmissão lateral por correias;
- Rotor reforçado Ø180mm - 2250rpm;
- Rotor com martelos dentados (furo Ø205mm);
- Chumaceiras profissionais c/ rolamentos oscilantes;
- Rolo nivelador traseiro;
- Correntes c/ lona em borracha para protecção frontal;
- Porta traseira de abertura mecânica;
- Patins de desgaste em HARDOX;
- Cardan reforçado (tubo estrela).